

SEPARATOR FOR BATTERY AND ITS MANUFACTURE AND BATTERY USING IT

Patent number: JP11297295
Publication date: 1999-10-29
Inventor: KIDA TATSUNOBU; YAMAMOTO HIROYUKI; HORI SHUJI; SAKAI TETSUO
Applicant: AGENCY IND SCIENCE TECHN;; DAIWA SPINNING CO LTD;; SAKAI TETSUO
Classification:
- international: H01M2/16; H01M10/24
- european:
Application number: JP19980092047 19980403
Priority number(s): JP19980092047 19980403

Report a data error here

Abstract of JP11297295

PROBLEM TO BE SOLVED: To provide a separator for a battery having excellent strength and liquid-holding property, capable of contributing to the improvement of a battery capacity without reducing a battery service life, by forming the separator with a porous sheet of non-woven fabric or the like, including fibers having a syndiotactic poly (1,2-butadiene) structure in the molecular structure with at least a part of the unsaturated linkages introduced with ion exchanging groups. **SOLUTION:** A resin component which has a syndiotactic poly (1,2-butadiene) structure in the molecular structure, and which is composed by introducing ion exchanging groups into at least a part of the unsaturated linkages, is confounded, among fibers, with fiber webs including synthetic fibers (A) which occupy at least a part of fiber surfaces, by high-pressure water-jet treating to form non-woven fabric, followed by a sulfonation treating thereto in comparatively mild conditions.

.....
Data supplied from the **esp@cenet** database - Worldwide